

| | | |
|---|---|-----------------|
|  | SONARtrac® Technical Bulletin | |
| | Subject: Use of Teflon Joint Sealant on Sensor Covers | No:TB002 |
| | | Priority: 5 |
| | | Date: 15 Jul 04 |

PCO# PO4-0022 calls for the use of CiDRA Corporation Part Number 52307-01 *Sealant, Pipe & Thread, PTFE Paste* on the Teflon seal on fiberglass covers. The sealant acts as a lubricant during initial installation of the cover, and also acts as a secondary seal against moisture entering the cover. The upper and lower cover seals are lightly coated with the sealant just before installation of the process pipe.

All fiberglass covers being shipped from CiDRA will have the sealant enclosed as part of the installation kit. Use of the sealant will be documented in the next revision of the P/N 20295-01 Sensor Installation Manual.

The sealant, manufactured by Fluoramics, Inc. of Mayway, New Jersey, is called “Formula-8 with Teflon Joint & Thread PTFE PASTE SEALER”. It is available through McMaster Carr as their Part Number 4538K1. Additional information on this sealant is available at the following website: www.tufoil.com/form8.html .

A Material Safety Data Sheet for the sealant is part of this bulletin.

Please contact CiDRA Customer Support at 203-265-0035 or customersupport@cidra.com for further information.

| Priority Code: | | | |
|-----------------------|--|---|---|
| 1 | Safety issue or system will not function | 2 | Intermittent problem causing system crash |
| 3 | Erratic data/readings | 4 | Added product feature |
| 5 | Product enhancement | | |

CiDRA Corporation
Tel. 203-265-0035

50 Barnes Park North
Fax. 203-294-4211

Wallingford, CT 06492
www.cidra.com

MATERIAL SAFETY DATA SHEET

IDENTITY: FORMULA-8 (Oxygen Compatible)

Chemical name: Aqueous Paste & Filler of PTFE
Chemical family: Perfluorocarbon Polymer
Formula: (CF)²ⁿ

MANUFACTURER: Fluoramics Inc.
ADDRESS: 18 Industrial Avenue
Mahwah, N.J. 07430
PHONE: 201-825-8110

DATE PREPARED: January,
2003
PREPARED BY: F.G. Reick,
President

CAS NUMBERS:

H₂O (water): No CAS number
Carboxy Vinyl Polymer: 9003 01 4
Polytetrafluoroethylene Powder: 9002 84 0
Polytetrafluoroethylene Aqueous Dispersion: 9002
84 0
Ti O₂ Titaniumdioxide: 13463 67 7
Monoethanolamine: 141 43 5

SECTION 1 - COMPONENTS

| COMPONENTS | % | ACHIH - TLV |
|---|----|------------------|
| Carbopol | 5 | |
| Pigments | 20 | TiO ² |
| Vehicle | 14 | Water |
| Surfactants - Triton 100 | 1 | |
| Teflon (PTFE) T30** | 59 | |
| Colloidal Silica | 1 | |
| **Inert to oxygen, non-combustible, odorless, no known dangerous mixtures | | |

SECTION 2 - PHYSICAL/CHEMICAL CHARACTERISTICS

Boiling point: 212° (water)
Vapor Pressure: less than 0.01
Vapor Density: N/A
Solubility in Water: Dispersible

Specific Gravity H₂O=1): 1.2
Melting Point: N/A
Evaporation Rate (butyl acetate=1): H₂O slow
Water Dispersable
Appearance and Odor: White paste - odorless

SECTION 3 - FIRE & EXPLOSION HAZARD DATA

Flash Point & Method Used: None
Flammability Limits in Air % by Volume: Non-combustible

Extinguisher Media: Incombustible

Special Fire Fighting Procedures: None

Unusual fire and Explosion Hazards: In extreme fire situation, protection from hydrogen fluoride fumes should be employed

| | NFPA CODES | HMIS CODES |
|---------------------|------------|------------|
| HEALTH | 1 | 1 |
| FLAMMABILITY | 0 | 0 |
| REACTIVITY | 0 | 0 |
| PERSONAL PROTECTION | SCBA | B |

SECTION 4 - REACTIVITY HAZARD DATA

Stability: Stable

Conditions to Avoid: Temperature above 250° without adequate ventilation.

Will not polymerize.

Incompatibility (Materials to Avoid): Strong alkali

Hazardous Decomposition Products: At 650°C (1202°), COF₂ is the principal toxic product. At above 650°C, major products are CF₄ and CO₂.

Hazardous Polymerization: Will not occur

SECTION 5 - HEALTH HAZARD DATA

Primary Routes of Entry: Inhalation - Skin - Ingestion

Health Hazards: Treat symptomatically

Signs and Symptoms of Exposure: PTFE polymer, when thermally decomposed, may cause polymer fume fever and flu-like symptoms.

Medical Conditions Generally Aggravated by Exposure: See below

Eye Contact: Wash with copious amounts of water.

Skin Contact: Remove by wiping and wash with soap and water

Inhalation: Remove to fresh air

Ingestion: contact a physician

Emergency First Aid Procedures: Call a physician.

SECTION 6 - CONTROL AND PROTECTIVE MEASURES

Respiratory Protection (Specify Type): If exposed to high temperature processing fumes, wear self-contained breathing apparatus.

Protective Gloves: Yes

Eye Protection: Goggles if contact is probable

Ventilation to be Used: Local exhaust preferred; General (mechanical), usually none
Other Protective Clothing and Equipment: Protective garment when applicable
Hygienic Work Practices: As indicated

SECTION 7 PRECAUTIONS FOR SAFE HANDLING AND USE LEAK PROCEDURES

Steps to be Taken if Material is Spilled or Released: N/A
Waste Disposal Methods: Land fill is preferred but disposal methods must conform with local state and federal regulations.
Precautions to be Taken in Handling and Storage: Strictly enforce NO SMOKING rule for workers handling material.
Other Precautions and/or Special Hazards: Use normal personal hygiene and good housekeeping.